

Hot Wire Anemometer

Features

- High accuracy for low wind speed measurement
- Slim probe for narrow space's wind speed / wind flow
- 2.7 inches double line display with backlight
- Built-in temperature sensor for fast response of temperature measurement
- Selectable wind speed unit / temperature unit



Model	ET-961		
Unit	Range	Resolution	Accuracy
M/S	0.1 ~ 25.0 m/s	0.01 m/s	+/- 5% +/-0.1 m/s
km/h	0.3 ~ 90.0 km/h	0.1 km/h	+/- 5% +/-0.1 km/h
ft/min	20 ~ 4925 ft/min	1 ft/min	+/- 5% +/-0.1 ft/min
MPH	0.2 ~ 55.8 MPH	0.1 MPH	+/- 5% +/-0.1 MPH
Knots	0.2 ~ 45.8 Knots	0.1 Knots	+/- 5% +/-0.1 Knots
Air Temperature	0 ~ 50°C/32 ~ 122°F	0.1°C/°F	+/-1.0°C / 1.8°F
CFM (CFM = ft ³ /min)	0 ~ 99999 ft ³ /min	0.001 ~ 100	
CFM (CFM = m ³ /min)	0 ~ 99999 m ³ /min	0.001 ~ 100	
Sampling Rate	0.8s		
Operating Temperature	-0 ~ 50°C / 32°F ~ 122°F		
Operating Humidity	< 80% RH		
Power Supply	6F 22 9V	Adapter	DC 9V 1A
Weight	310g	Dimension	185 x 66 x 33 mm