

Type K Digital Thermometer

Features

- Single Channel
- Resolution: 0.1°C / 0.1°F , 1°C / 1°F
- Data Hold
- Max Hold
- °C and °F Selection
- Large LCD Display of 3-1/2 digits with 1999 counts
- Input Protection – 60V DC or 24V rms AC Maximum
- Low Battery indicator



Model	DE-3003
Measuring Range:	-50°C ~ 1300°C (-58°F ~ 1999°F)
Supplied Probe	4-foot Type K thermocouple bead probe (Teflon tape insulated). Max insulation temperature - 260°C (500°F)
Accuracy	Range of 18°C to 28°C (64°F to 82°F) +/- (0.3% rdg + 1°C) -50°C to 1000°C +/- (0.5% rdg + 1°C) 1000°C to 1300°C +/- (0.3% rdg + 2°F) -58°F to 1999°C
Probe Accuracy	+/- 2.2°C or +/- 0.75% rgd (whichever is greater) from 0°C to 800°C
Ambient Operating Range	0°C to 50°C (32°F to 122°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Reading Rate	2.5 times per second
Power Supply	Standard 9V Battery (NEDA 1604, IEC 6F22)
Dimension	148 x 71 x 36mm
Weight	Approx. 210g